

Zehnder ComfoConnect KNX C

**Zehnder ComfoConnect KNX C for Zehnder ComfoAir
Q350/450/600**

Product data sheet

always the best climate



ComfoConnect KNX C

Product code: 655 011 120



The Zehnder ComfoConnect KNX C enables the connection between the ventilation system and the KNX building management system.

Key Benefits

- Control and monitor the ventilation system via the KNX building management system
- Control ventilation flow rate, temperature profile, temporary high speed setting and external sensor set points
- Monitor ventilation flow rates, temperatures and external sensors
- 7 day flow rate programmer
- Service and Maintenance alert
- ETS5 compatible

Technical Specification		Dimensions
Supply voltage	Low voltage direct from the MVHR units ComfoNET connector	Dimensions (surface mounted)
IP rating	IP30	Height 120 mm
Recommended cable	4 core cable, 1 mm Max. (up to 50 metres)	Width 76 mm
RAL colour	Front: 9003 Back: 7024	Depth 25 mm
Device model	System B	
Supported configuration mode	S-Mode	
Supported ETS version	5	
Zehnder KNX library available at	https://www.zehnder.co.uk	
Maximum number per unit	1	

For use with	
Description	Product code
Suitable for use with MVHR units:	
Zehnder ComfoAir Q350	471502015
Zehnder ComfoAir Q350 with pre-heater, right handed	471502016
Zehnder ComfoAir Q350 with pre-heater, left handed	471502017
Zehnder ComfoAir Q350 with enthalpy exchanger	471502018
Zehnder ComfoAir Q450	471502019
Zehnder ComfoAir Q450 with pre-heater, right handed	471502020
Zehnder ComfoAir Q450 with pre-heater, left handed	471502021
Zehnder ComfoAir Q450 with enthalpy exchanger	471502022
Zehnder ComfoAir Q600	471502023
Zehnder ComfoAir Q600 with pre-heater, right handed	471502024
Zehnder ComfoAir Q600 with pre-heater, left handed	471502025
Zehnder ComfoAir Q600 with enthalpy exchanger	471502026