

# Shower toilet seat and cover, with hidden connections, with remote control 89289.1



## TECHNICAL DATA

Order no.	89289.1
Certified to	CE, IPX4, EN1717
matching for	Floorstanding WC pan Laufen Pro, order no. 822956 000 S00 1 Wallhung WC pan Laufen Pro, order no. 821962 000 S00 1, 821966 000 S00 1
Specifications	Duroplast, with hidden connections, with antibacterial treatment, with lowering system Lid with quick release function for cleaning Electric Bidet easy to lift for cleaning iOS and android app. connection
Water inlet	G 3/8" (male)
Working pressure	0.1 to 0.7 Mpa (1-7 bar)
Working temperature	+5 to +35 °C
Cleaning functions	Rear shower and lady shower 5 levels pressure adjustment 5 levels nozzle position adjustment 5 levels temperature adjustment Oscillating and pulsating cleaning mode
Dryer function	5 levels temperature adjustment Oscillating drying mode
Seat heating	5 levels temperature adjustment
Comfort	Night light (bowl and ambience) Remote operation 5 user profiles Integrated descaling function
Hygiene	Self cleaning of shower head before and after every use Exchangeable shower head UV nozzle disinfection
Power supply & consumption	Rated voltage 220-240V, 50/60Hz Power consumption in use max. 1650W Power saving mode Power cord length 1m

Weight	7,8 kg
Accessories incl.	Remote control with rotary button for shower function, with AAA batteries and wall holder with anti-thief system Splash protection User manual
Mounting acc. incl.	Mounting instruction Installation template, order no. WK2ES42004002 Mounting set incl. fastening kit, order no. 89389.3
Mounting acc. excl.	Fastening kit Direct electrical connector, order no. 89F89.2 Electro cable with EU-plug (type F), order no. 89E89.0 Electro cable with CH-plug (type J), order no. 89E89.1
Colours	000 – White

## SPECIFICATION TEXT

Shower toilet seat and cover, with remote control Laufen  
CLEANET PRO,

Duroplast, with hidden connections, with antibacterial treatment,  
lid with quick release function for cleaning, seat with heating type  
CE, IPX4, EN1717, rated voltage 220-240V, 50/60Hz  
dimensions 370 x 490 x 85 mm

Special feature: remote control, rear shower and lady shower, with  
adjustable water pressure, temperature and nozzle position, oscillating  
and pulsating cleaning mode, self cleaning of shower head before and  
after every use, exchangeable shower head, UV nozzle disinfection,  
Integrated descaling function, heated seat with adjustable temperature  
and soft closing lid and seat, integrated night light, power saving mode,  
5 user profiles, iOS and android app. connection

Order no. 89289.1

## Shower toilet seat and cover, with hidden connections, with remote control 89289.1



### TECHNICAL DRAWINGS / S 1 : 20

